THE COMMANDER SERIES

Commander 7000X

The Dannmar Commander 7000X four-post vehicle lift is the extended version of the Commander 7000, with 7,000 lbs lifting capacity. Designed to work with a wider variety of vehicles, the Commander 7000X is a longer, wider and taller version of the standard Commander 7000. Having that extra room can make all the difference for a car collector or someone needing more parking spaces. The Commander 7000X four-post lift is perfect for that exact application. It features a single point safety handle and a very durable hydraulic pump assembly.

If you have the room, purchase the Commander 7000X. It will give a wider range of flexibility with cars and trucks.

FEATURES

* Dannmar Commander 7000X four-post lift is extra wide
* Simple controls make for an easier operation
* Spring loaded safety locks are located on each column
* Self-lubricating UHMW polyethylene internal slide blocks are also located in each column
* Features a single safety lock release handle
* Bulky single hydraulic cylinder is located underneath runway for added room
* Reliable electric/hydraulic power unit assembly
* The drive-up ramps are detachable when needed
* Designed to be free standing
* Self-lubricating bearings and cable sleeves
* Runways include rail-kit as an optional accessory

OPTIONS

* Caster Kit
* Jack Platform
* Plastic Drip trays
* Aluminum (Lightweight) Drive Up Ramps
* Steel Deck (Fills the Center of the lift)
* Aluminum Deck (Fills the Center of the lift)
* Cycle Vise (Motorcycle Adaptor attaches to Runway)

SPECIFICATIONS

* **Lifting Capacity:** 7,000 lbs. / 3182 kg.
* **Overall Width:** 117” / 2972 mm.
* **Outside Length:** 194-1/2” / 4940 mm.
* **Overall Length:** 227-1/2” / 5779 mm.
* **Height Columns:** 94” / 2388 mm.
* **Minimum Runway Height:** 4-1/2” / 114 mm.
* **Maximum Rise:** 85” / 2159 mm.
* **Maximum Lifting Height:** 89” / 2261 mm.
* **Width Between Columns:** 103” / 2616 mm.
* **Runway Width:** 18-1/2” / 470 mm.
* **Width Between Runways:** 37-1/2” / 953 mm.
* **Length of Runways:** 185” / 4699 mm.
* **Locking Positions:** 13
* **Clearance At Each Locking Position: 1.** 17” **2.** 32.5” **3.** 37” **4.** 41.5” **5.** 46” **6.** 50.5” **7.** 55” **8.** 59.5” **9.** 64” **10.** 68.5” **11.** 73” **12.** 77.5 **13.** 82”
* **Lock Spacing:** Every 4-1/2”
* **Lifting Time:** 45 Seconds
* **Standard Motor:** 110 VAC 60Hz. 1Ph

646 Flinn Avenue, Suite A, Moorpark, CA 93021 | 877.432.6627 | www.dannmar.com

*Please note that these specifications are subject to change without notice. It is best to confirm these specifications with a sales representative at the time of purchase.