



THE ADMIRAL SERIES

Admiral 9000X



The Admiral 9000X is the extended version of the Admiral 9000 two-post automotive lift, providing over a foot more in width between posts and drive through clearance than the standard version. This floor-plate garage lift offers serious benefits that make it very desirable to both the service technician, business owner, and the home owner.

This vehicle lift is extra-wide for those larger vehicles, and its extended arm reach will cover most vehicle lifting points. The Admiral 9000X has a low-profile design which is perfect for shops and garages with height restrictions.

FEATURES

- * Dannmar Two-post Vehicle Lifts 9,000 lbs lifting capacity
- * Low column height accommodates low-ceiling installations
- * Maximum lifting height provides 6 feet of under-car clearance
- * Able to raise high profile vehicles with no restrictions
- * Maintenance-free, "Dura-Glide" polyethylene load bearings
- * Single-piece columns for added strength and less fatigue
- * Dual hydraulic cylinders combined with "chain over" lifting system provides 2-to-1 lifting speed and rugged dependability
- * Dual-Synchro equalization system maintains equal lifting
- * Heavy-duty lift arms feature automatic safety restraints
- * Comes standard with eight piece truck and van adapter set
- * A low-profile bottom cover plate means easier vehicle positioning
- * Includes detailed installation and maintenance instructions, graphic safety and maintenance decals, and a vehicle lifting point guide and safety instruction placard guidelines
- * Oversize column base plates provide strong support
- * Safety locks in each column spaced every three inches
- * Heavy-duty 3/8" and 1/2" equalizer cables
- * Convenient storage is included for truck and van adapters

SPECIFICATIONS

- * **Lifting Capacity:** 9,000 lbs. / 4091 kg.
- * **Overall Height:** 113" / 2870 mm.
- * **Overall Width (Outside of Base plates):** 145" / 3683 mm.
- * **Overall Width (Outside of Columns):** 137" / 3480 mm.
- * **Floorplate Height:** 2" / 51 mm.
- * **Width Between Columns:** 118" / 2997 mm.
- * **Minimum Reach (Front Arm):** 35" / 889 mm.
- * **Maximum Reach (Front Arm):** 52" / 1321 mm.
- * **Minimum Reach (Rear Arm):** 35" / 889 mm.
- * **Maximum Reach (Rear Arm):** 52" / 1321 mm.
- * **Minimum Pad Height:** 4" / 102 mm.
- * **Rise:** 74" / 1880 mm.
- * **Maximum Lifting Height (Pad Only):** 76" / 1930 mm.
- * **Maximum Lifting Height (Pad & 6" Adapter):** 82" / 2083 mm.
- * **Drive Thru Clearance:** 109" / 2769 mm.
- * **Lifting Time:** 45 seconds
- * **Maximum Load Per Arm:** 2,250 lbs. / 1023 kg.
- * **Motor:** 220 VAC 60Hz. 1Ph

