



THE BRIGADIER SERIES

Brigadier 10ACX



Dannmar is constantly striving to increase its product line to further provide customers with versatility and options. We decided to add this wider version of the Brigadier 10ACX for wider vehicles and drive-thru clearance. Still an asymmetric two-post lift, the posts are rotated 30 degrees and spaced further apart giving you the ability to open car doors without the dents. This two-post lift will be an asset to any repair facility it is installed in. In addition, this lift can be angled in narrow repair bays to accommodate other lifts.

One of Dannmar's highest selling two-post lift models, the Brigadier 10ACX will out-perform others in its class at a highly affordable cost. Everything from the "Dura-Glide" polyethylene load bearings, to the heavy duty 3/8" equalizer cable have been carefully chosen for long lasting operation.

FEATURES

- * Dannmar Two-post Vehicle Lifts 10,000 lbs lifting capacity
- * Wide or narrow configuration
- * Specifically designed with posts that are rotated in 30 degrees to offset the vehicle center point back for ease of entry into the vehicle
- * Narrow space saving design works perfectly in almost any sized repair bay
- * Dual-Synchro equalization system maintains equal lifting
- * Maintenance-free, "Dura-Glide" polyethylene load bearings
- * Single-piece columns for added strength and less fatigue
- * Dual hydraulic cylinders combined with "direct-drive" lifting system provides 2-to-1 lifting speed and rugged dependability
- * Heavy-duty lift arms feature automatic safety restraints
- * Comes standard with eight piece truck and van adapter set
- * Includes detailed installation and maintenance instructions, graphic safety and maintenance decals, and a vehicle lifting point guide and safety instruction placard guidelines.
- * Oversize column base plates provide strong support
- * Safety locks in each column spaced every three inches
- * Heavy-duty 3/8" equalizer cables
- * Convenient storage is included for truck and van adapters

SPECIFICATIONS

- * **Lifting Capacity:** 10,000 lbs. / 4546 kg.
- * **Style:** Wide Asymmetric
- * **Overall Height:** 145" / 3683 mm.
- * **Overall Width (Outside of Base plates):** 143 1/2" / 3644.9 mm.
- * **Overall Width (Outside of Columns):** 136 1/2" / 3467.1 mm.
- * **Width Between Columns:** 112 3/4" / 2863.9mm.
- * **Minimum Reach (Front Arm):** 25" / 635 mm.
- * **Maximum Reach (Front Arm):** 46" / 1168 mm
- * **Minimum Reach (Rear Arm):** 42" / 1067 mm
- * **Maximum Reach (Rear Arm):** 60" / 1524 mm.
- * **Minimum Pad Height:** 4-1/2" / 114 mm.
- * **Rise:** 69" / 1753 mm.
- * **Maximum Lifting Height (Pad Only):** 73" / 1854 mm.
- * **Maximum Lifting Height (Pad & 6" Adapter):** 79" / 2007 mm.
- * **Drive Thru Clearance:** 100 1/2" / 2552.7 mm.
- * **Lifting Time:** 45 seconds
- * **Maximum Load Per Arm:** 2,500 lbs. / 1023 kg.
- * **Motor:** 220 VAC 60Hz. 1Ph

